

## **About Xsens DOT**

Xsens DOT is a state-of-the-art development platform for the measurement and analysis of human kinematics from industry leaders, Xsens. The platform features high-accuracy wearable inertial sensors, an easy-to-integrate mobile SDK and community support from Xsens experts.

Xsens DOT provides endless application possibilities for innovators and developers giving everything needed to build a commercially attractive application.

## Make it happen with Xsens DOT

Visit www.xsens.com/xsens-dot



GENERAL	
SENSOR PLACEMENT	Application dependant Straps, holders and sleeves available by Xsens (sold separately)
LATENCY	30 ms
BATTERY	Battery life up to 6 hrs Charging time about 1 hr
WEIGHT	11.2 g
DIMENSIONS SENSOR	36.30 x 30.35 x 10.80 mm (l x w x h)
OPERATING TEMPERATURE RANGE	0°C - 50°C
WATERPROOF RATING	IP 68
INTERNAL STORAGE	64 MB
COMMUNICATION	
COMMUNICATION PROTOCOL	Best performance with Bluetooth 5.0 devices or above
SUPPORTED OPERATION SYSTEMS	Android OS 8.0 or above iOS 11.0 or above Windows 10 or above Linux (Ubuntu 20.04 or 22.04)
COMPATIBLE DEVICES	Any (via BLE 5.0)

ORIENTATION		
STATIC	0.5°   1.0° 1σ RMS	
(INCLINATION   HEADING)		
DYNAMIC	1.0°   2.0° 1σ RMS	
(INCLINATION   HEADING)		
SENSOR COMPONENTS		
FULL SCALE	± 2000%   ± 16g   ± 8 Gauss	
DIMENSIONS	3 axes	
	Orientation (Unit Quaternions & Euler Angles)	
	Free acceleration	
DATA OUTPUT	Acceleration	
	Angular Velocity	
	Magnetic Field	
	Timestamp and status	
REAL-TIME	1Hz, 4Hz, 10Hz, 12Hz, 15Hz, 20Hz, 30Hz and 60Hz	
RECORDING	1Hz, 4Hz, 10Hz, 12Hz, 15Hz, 20Hz, 30Hz, 60Hz and 120Hz	