



| | | | |
|-----------------------------------------------------|-----------------------------------------------|----------------------------------|------------------------------------|
| Image Sensor | 2048 × 2048 Resolution | 360 Hz Native Frame Rate | 2.8 ms Latency |
| Tracking Performance & Range¹ | 3D Accuracy +/- 0.15 mm | Passive Markers 21 m (70') | Active Markers 30 m (100') |
| Global Shutter | Default Speed 0.25 ms | Minimum Speed 0.01 ms | Maximum Speed 2.5 ms at 360 fps |
| Image Processing Types | Object Segment | Raw Greyscale MJPEG Grayscale | |
| Connections | GigE data port | PoE or PoE+ ¹ power | Ethernet camera sync |
| Lens & Filter | Stock Lens 79° × 49° FOV | Adjustable Focus | Adjustable f-stop |
| LED Ring | 20 LEDs Ultra High Power 850nm Infrared | Strobe Mode Intensity control | |

Size & Weight



Width

4.96 inches (12.6 cm)

Height

4.96 inches (12.6 cm)

Depth

4.19 inches (10.7 cm)

Weight

2.77 pounds (1.26 kg)

Camera Body

Aluminum &
Polycarbonate

1/4"-20 Standard
Tripod Mount (×2)

2 digit numeric LEDs
status indicators

Full-color LED health
and activity indicator